



Standard Resonators

	TIP ROD LENGTH	BANDWIDTH (AT 2:1 SWR OR BETTER)
RM-1	12 5/8"	150 - 250 KHz
RM-11	12 5/8"	150 - 250 KHz
RM-12	18 7/16"	100 - 150 KHz
RM-15	12 5/8"	100 - 150 KHz
RM-17	23 1/4"	80 - 100 KHz
RM-20	18 7/16"	80 - 100 KHz
RM-30	18 7/16"	50 - 60 KHz
RM-35	40 1/8"	50-60 KHz.
RM-40	32 1/8"	40 - 50 KHz
RM-50	40 1/8"	40-50 KHz.
RM-75	32 1/8"	25 - 30 KHz
RM-80	40 1/8"	25 - 30 KHz

Standard Resonator

Super Resonators

	TIP ROD LENGTH	BANDWIDTH (AT 2:1 SWR OR BETTER)
RM-10S	12 13/16"	250-400 KHz
RM-11S	18 5/8"	250-400 KHz
RM-15S	16 5/16"	150-200 KHz
RM-20S	18 5/8"	100-150 KHz
RM-40S	32 5/16"	50-80KHz
RM-75S	32 5/16"	50-60 KHz
RM-80S	40 5/16"	50-60 KHz

Super Resonator

